

➔ WATERPROOF HEATED BACKUP CAMERA:



RDC-004HD

➔ 7" HD TOUCH SCREEN LCD COLOUR MONITOR:



RDV-7LCDHD

FEATURES

RESOLUTION:	1080P high definition
IP RATING:	IP69K waterproof
WIDE VIEWING ANGLE:	130°
NIGHT VISION DISTANCE:	8m~10m (26.25ft~32.81ft)
WIDE POWER SUPPLY:	DC 12V / DC10~32V
ANTI-VIBRATION:	ISO 16750-3 (Max. 17.3G)
MIRROR:	Normal image switchable
SMART-IR:	Optional
WORKING TEMPERATURE:	-20°C ~ +70°C

SPECIFICATIONS

IMAGE DEVICE:	1/2.9" CMOS
FRAME RATE:	25 fps / 30 fps
EFFECTIVE PIXELS:	1920(H) x 1080(V)
PIXEL SIZE:	2.8 μm x 2.8μm
SCANNING SYSTEM:	Progressive Scanning
SYNC. SYSTEM:	Internal
RESOLUTION:	1080P
VIDEO OUTPUT:	1.0Vp-p, 75Ohm
GAMMA CONSUMPTION:	0.45
AGC:	Auto
S/N RATIO:	Better than 52dB
WHITE BALANCE:	Auto
ELECTRONIC SHUTTER:	1/25 (1/30) ~ 1/50,000 Seconds
BLC:	Auto
OPERATING TEMPERATURE:	-20°C~70°C, RH 95% MAX.
STORAGE TEMPERATURE:	-30°C~80°C, RH 95% MAX.

FEATURES

SUPPORT:	4CH x 1080P / 720P cameras
VIDEO INPUT:	4 x Aviation Ports, 4 x Triggers
CONTROL:	Touch screen and IR remote control
AUTOMATED VIEW:	Trigger priority
SUPPORT:	Auto Scan
CONTRAST:	800:1
RESOLUTION:	1024*600
BRIGHTNESS:	800cd/m2
POWER SUPPLY:	DC 10-32V

SPECIFICATIONS

RESOLUTION:	1024 x 3(RGB) x 600
ANTI-VIBRATION:	ISO 16750-3 Max. 6.3G
MAX. NUMBER OF CAMERAS:	4
AUDIO INPUT:	4
AUDIO OUTPUT (LOUDSPEAKER) :	1W
TRIGGER:	5
MAX. BRIGHTNESS:	800 cd/m ²
CONTRAST:	800 : 1
MIN. OPERATING TEMPERATURE:	-20°C, RH 90%
MAX. OPERATING TEMPERATURE:	+70°C, RH 90%
VIEWING ANGLE MONITOR:	U: 70/ D: 75, R/L: 75/75
MONITOR DIAMETER (MM):	203mm (W) x 112mm (H) x 28mm (T)
SPLIT SCREEN:	No
VOLTS:	10-32V
CONSUMPTION:	Less than 6W (without cameras)