

### ➔ WIDE-ANGLE FRONT VIEW CAMERA:



RDC-308

### FEATURES

<b>RESOLUTION:</b>	1080P HD
<b>WDR:</b>	120db (Max)
<b>WATERPROOF:</b>	No
<b>WIDE VIEWING ANGLE:</b>	170°
<b>POWER SUPPLY:</b>	DC 12V / DC10~32V
<b>ANTI-VIBRATION:</b>	ISO 16750-3 4.1.2.7: 2012
<b>WORKING TEMPERATURE:</b>	-20°C ~ +70°C

### SPECIFICATIONS

<b>IMAGE DEVICE:</b>	1/2.8" CMOS
<b>FRAME RATE:</b>	25 fps / 30 fps
<b>EFFECTIVE PIXELS:</b>	1920 (H) x 1080 (V)
<b>PIXEL SIZE:</b>	2.9 μm x 2.9 μm
<b>SCANNING SYSTEM:</b>	Progressive Scanning
<b>SYNC. SYSTEM:</b>	Internal
<b>RESOLUTION:</b>	1080P
<b>WATERPROOF RATING:</b>	Non Waterproof
<b>VIEWING ANGLE:</b>	170° / 130° / 110° / 100° / 65°
<b>MICROPHONE/AUDIO:</b>	Yes
<b>MIINIMUM ILLUMINATION:</b>	0.1 Lux
<b>WDR:</b>	120db
<b>IMAGE MODE:</b>	Normal
<b>VIDEO OUTPUT:</b>	1.0Vp-p, 75Ohm
<b>GAMMA CONSUMPTION:</b>	0.45
<b>AGC:</b>	Auto
<b>WHITE BALANCE:</b>	Auto
<b>ELECTRONIC SHUTTER:</b>	1/30 (1/25)~1/50,000 Seconds
<b>BLC:</b>	Auto
<b>OPERATING TEMPERATURE:</b>	-20°C ~ 70°C, RH 95% MAX.
<b>STORAGE TEMPERATURE:</b>	-30°C ~ 80°C, RH 95% MAX.

Revised: June 2020