

➔ 7" TOUCH SCREEN:



RDV-7LCDHD

FEATURES

SUPPORT:	4CH x 1080P / 720P cameras
VIDEO INPUT:	4 x Aviation Ports, 4 x Triggers
CONTROL:	Touch screen and IR remote control
AUTOMATED VIEW:	Trigger priority
SUPPORT:	Auto Scan
CONTRAST:	800:1
RESOLUTION:	1024*600
BRIGHTNESS:	800cd/m2
POWER SUPPLY:	DC 10-32V

SPECIFICATIONS

RESOLUTION:	1024 x 3(RGB) x 600
ANTI-VIBRATION:	ISO 16750-3 Max. 6.3G
MAX. NUMBER OF CAMERAS:	4
AUDIO INPUT:	4
AUDIO OUTPUT (LOUDSPEAKER) :	1W
TRIGGER:	5
MAX. BRIGHTNESS:	800 cd/m ²
CONTRAST:	800 : 1
MIN. OPERATING TEMPERATURE:	-20°C, RH 90%
MAX. OPERATING TEMPERATURE:	+70°C, RH 90%
VIEWING ANGLE MONITOR:	U: 70/ D: 75, R/L: 75/75
MONITOR DIAMETER (MM):	203mm (W) x 112mm (H) x 28mm (T)
SPLIT SCREEN:	No
VOLTS:	10-32V
CONSUMPTION:	Less than 6W (without cameras)

➔ 10" TOUCH SCREEN QUAD-VIEW:



RDM-QUAD10HD

FEATURES

SUPPORT:	4CH x 1080P or 720P cameras
VIDEO INPUT:	1 x VGA, 1 x DVD
CONTROL:	Touch screen, L/R "swipe" channel switching
AUTOMATED VIEW:	Trigger priority
SUPPORT:	Auto scan, user pre-set scan channel/time
CONTRAST:	600:1
RESOLUTION:	1024*600
BRIGHTNESS:	600cd/m2 , L-5 manual adj, L-3 auto adjust
POWER SUPPLY:	DC 10-32V
ALSO AVAILABLE IN:	7" RDV-QUAD7HDT

SPECIFICATIONS

RESOLUTION:	1024 x 3(RGB) x 600
ANTI-VIBRATION:	ISO 16750-3 Max. 6.3G
MAX. NUMBER OF CAMERAS:	4
AUDIO INPUT:	4
AUDIO OUTPUT (LOUDSPEAKER) :	1W
VGA INPUT	1
DVD INPUT	1
MIRROR FUNCTION	Yes
TRIGGER:	5
MAX. BRIGHTNESS:	600 cd/m ²
CONTRAST:	600 : 1
MIN. OPERATING TEMPERATURE:	-20°C, RH 90%
MAX. OPERATING TEMPERATURE:	+70°C, RH 90%
VIEWING ANGLE MONITOR:	U: 70/ D: 75, R/L: 75/75
MONITOR DIAMETER (MM):	267mm (W) x 159.5mm (H) x 30mm (T)
SPLIT SCREEN:	Yes
VOLTS:	10-32V
CONSUMPTION:	MAX 25W, less than 12W (no cameras)

➔ 5" MONITOR:



RDM-05B

FEATURES

SUPPORT:	TFT LCD display with wide viewing angle
VIDEO INPUT:	3 channel, 3 reverse trigger wire
CONTROL:	Full-function remote/span
PICTURE IMAGE(S):	Vertical, mirror, non-mirror viewing
SUPPORT:	Mechanical buttons, backlighting
SPEAKER:	Control panel volume adjustment
BACKLIGHT:	Automatic adjustment
POWER SUPPLY:	DC 10-32V, support 12V or 24V automobile battery
ALSO AVAILABLE IN:	5"HD-1080P RDM-05HD

SPECIFICATIONS

RESOLUTION:	640 x 3(RGB) x 480
AUDIO OUTPUT:	1W
LOUDSPEAKER:	One 4.0cm round loudspeaker
OUTER DIMENSION:	157mm (W) x 112mm (H) x 32mm
DOT PITCH:	0.053(W) x 0.159 (H)
CONTRAST :	500:1
BRIGHTNESS:	250cd/m ²
VIEWING ANGLE:	U: 50°, D: 70°, R/L: 70°/70°
POWER SUPPLY:	Automobile storage battery (10-32V)
POWER CONSUMPTION:	About 8W
OPERATING TEMPERATURE:	-20°C~+70°C, RH90%
STORAGE TEMPERATURE:	-30°C~+80°C, RH90%

➔ 7" WATERPROOF MONITOR



RDV-007W

FEATURES

SUPPORT:	TFT LCD display with wide viewing angle
IP RATING:	IP66
VIDEO INPUT:	up to 3
FORMAT:	AUTO/PAL/NTSC, 8 languages
CONTROL:	Full-function remote, touch button
PICTURE IMAGE(S):	Horizontal, vertical, mirror, non-mirror viewing
CAMERA VIEWS:	Automatic, backup, left or right, auto scan
SPEAKER:	Control panel volume adjustment
BACKLIGHT:	Automatic for buttons
BRIGHTNESS CONTROL:	Automatic
POWER SUPPLY:	DC 10-32V, support 12V or 24V automobile battery

SPECIFICATIONS

RESOLUTION:	800 x 3(RGB) x 480
AUDIO OUTPUT:	1.5W
LOUDSPEAKER:	One 15x24mm round loudspeaker
OUTER DIMENSION:	197.2mm (W) x 132mm (H) x 30.5mm
DOT PITCH:	0.0642(H) x 0.1790 (V)
CONTRAST :	500:1
BRIGHTNESS:	400cd/m ²
VIEWING ANGLE:	U: 50°, D: 70°, R/L: 70°/70°
POWER SUPPLY:	Automobile storage battery (10-32V)
POWER CONSUMPTION:	About 6W
OPERATING TEMPERATURE:	-20°C~+70°C, RH90%
STORAGE TEMPERATURE:	-30°C~+80°C, RH90%