

➔ WATERPROOF HEATED BACKUP CAMERA:



RDC-004HD

FEATURES

RESOLUTION:	1080P High Definition
IP RATING:	IP69K Waterproof
WIDE VIEWING ANGLE:	130°
NIGHT VISION DISTANCE:	8m~10m (26.25ft~32.81ft)
WIDE POWER SUPPLY:	DC 12V / DC10~32V
ANTI-VIBRATION:	ISO 16750-3 (Max. 17.3G)
MIRROR:	Normal Image Switchable
SMART-IR:	Optional
WORKING TEMPERATURE:	-20°C ~ +70°C

SPECIFICATIONS

IMAGE DEVICE:	1/2.9" CMOS
FRAME RATE:	25 fps / 30 fps
EFFECTIVE PIXELS:	1920(H) x 1080(V)
PIXEL SIZE:	2.8 μm x 2.8μm
SCANNING SYSTEM:	Progressive Scanning
SYNC. SYSTEM:	Internal
RESOLUTION:	1080P
VIDEO OUTPUT:	1.0Vp-p, 75Ohm
GAMMA CONSUMPTION:	0.45
AGC:	Auto
S/N RATIO:	Better than 52dB
WHITE BALANCE:	Auto
ELECTRONIC SHUTTER:	1/25 (1/30) ~ 1/50,000 Seconds
BLC:	Auto
OPERATING TEMPERATURE:	-20°C~70°C, RH 95% MAX.
STORAGE TEMPERATURE:	-30°C~80°C, RH 95% MAX.

➔ SUPER WIDE-ANGLE MINI BACKUP CAMERA:



RDC-306

FEATURES

RESOLUTION:	1080P High Definition
IP RATING:	IP69K Waterproof
VIEWING ANGLE:	190°/170°
POWER SUPPLY:	DC 12V
ANTI-VIBRATION:	ISO 16750-3 (Max. 17.3G)
WORKING TEMPERATURE:	-20°C ~ +70°C

SPECIFICATIONS

MINIMUM ILLUMINATION:	0.01Lux
MICROPHONE/AUDIO:	No
LENS:	f = 1.4mm / f = 1.98 mm
FRAME RATE:	25/30fps
EFFECTIVE PIXELS:	1920 (H) X 1080 (V)
PIXEL SIZE:	2.8umx2.8um
SCANNING SYSTEM:	Progressive Scanning
SYNC. SYSTEM:	Internal
VIDEO OUTPUT:	0.9Vp-p, 75Ohm
GAMMA CONSUMPTION:	0.45
AGC:	Auto
S/N RATIO:	S/N(a-weighted) 38dB
WHITE BALANCE:	Auto
BLC:	Auto
OPERATING TEMPERATURE:	-20°C~70°C, RH95%MAX.
STORAGE TEMPERATURE:	-30°C~80°C, RH95%MAX.

➔ WATERPROOF LICENSE PLATE CAMERA:



RDC-LICSHD

FEATURES

RESOLUTION:	1080P High Definition
IP RATING:	IP69K Waterproof
WIDE VIEWING ANGLE:	150°
NIGHT VISION DISTANCE:	5m (16.40ft)
POWER SUPPLY:	DC12V / DC10~32V
ANTI-VIBRATION:	ISO 16750-3 (Max. 17.3G)
DISTANCE LABEL:	Selectable to be Open or Closed
HOUSING:	Metal
ALSO AVAILABLE IN NON-HD:	RDV-LICS

SPECIFICATIONS

IMAGE DEVICE:	1/2.9" Colour CMOS
MINIMUM ILLUMINATION:	0.1 Lux (day), 0 Lux (with IR)
MICROPHONE/AUDIO:	Yes
LENS:	f=1.98mm, F=2.0
FRAME RATE:	25fps / 30fps
EFFECTIVE PIXELS:	1920 x 1080 pixels
PIXEL SIZE:	2.8um x 2.8um
SCANNING SYSTEM:	Progressive Scanning
SYNC. SYSTEM:	Internal
VIDEO OUTPUT:	1.0 Vp-p, 75 Ohm
GAMMA CONSUMPTION:	0.45
AGC:	Auto
S/N RATIO:	Better than 52 dB
WHITE BALANCE:	Auto
ELECTRONIC SHUTTER:	1/30(1/25)~ 1/50,000 Seconds
BLC	Auto
OPERATING TEMPERATURE:	-20 - +70°C RH95%MAX
STORAGE TEMPERATURE:	-30 - +80°C RH95%MAX
CURRENT CONSUMPTION:	Max. 130mA

➔ MINI PARK ASSIST CAMERA:



RDC-2213

FEATURES

- MAKING PARKING EASIER AND SAFER
- CIRCUIT PROTECTION FUNCTION
- EASY TO INSTALL
- ADJUSTABLE BRACKET

SPECIFICATIONS

RESOLUTION:	420 / 480
IP RATING:	IP67
VOLTAGE:	DC 12V
LENS ANGLE:	170 degree
CAMERA DIMENSIONS (MM):	23.5 x 23.7 x 22.17
BRACKET DIMENSIONS (MM):	40L x 22W